



1219 4th Avenue South  
Nashville, TN 37210


**Phone:** (615) 254-3561  
**Fax:** (615) 255-7673  
**Email:** sales@richeycap.com  
**Web:** richeycap.com

# RHE2R2M400V1012B

Aluminum Electrolytic Capacitors

Miniature Type  
RHE Series

Richey P/N: RHE2R2M400V1012B



## Specifications:

Dimensions:

Case Size D x L (mm): 10 x 12.5

Operating Temperature Range: -40-105 °C

Rated Voltage: 400 VDC

Surge Voltage: 450 VDC

Capacitance ( $\mu\text{F}$ ): 2.2

Leakage Current: 135.2

Rated Ripple Current: 140 mA rms @ +105°C, 100kHz

Typical ESR (m $\Omega$ ): 27 @ +20°C, 120Hz

Max ESR (m $\Omega$ ): 72.4 @ +20°C, 120Hz

Load Life:

Case Size            6.3×11.5 d - 8~10 d >12.5

Load Life in Hours    5000        8000        10000

Capacitance Change: Within +/- 30% of the initial measured value.

Dissipation Factor ( $\tan\delta$ ): Not more than 300% of the initial specified value

Leakage Current: Not more than initial specified value

\*ROHS Compliant