



1219 4th Avenue South
Nashville, TN 37210

Phone: (615) 254-3561
Fax: (615) 255-7673
Email: sales@richeycap.com
Web: richeycap.com

RPT121M063V0820B

Aluminum Electrolytic Capacitors

Miniature Type
RPT Series

Richey P/N: RPT121M063V0820B



Specifications:

Dimensions:

Case Size D x L (mm): 8 x 20

Operating Temperature Range: -40-105 °C

Rated Voltage: 63 VDC

Surge Voltage: 79 VDC

Capacitance (µF): 120

Leakage Current: 75.6

Maximum Ripple Current: 362 mA rms @ +105°C, 100kHz

Maximum Impedence: 0.33 @ +20°C, 100kHz

Load Life:

| Case Size > | d - 5~6.3 | d - 8~10 | d - 12.5~18 |
|-----------------|-----------|----------|-------------|
| Voltage Range v | | | |
| 6.3 ~ 10 | 4000 | 6000 | 8000 |
| 16 ~ 100 | 5000 | 7000 | 10000 |

Capacitance Change: Within +/- 25% of the initial measured value.

Dissipation Factor (tanδ): Not more than 200% of the initial specified value

Leakage Current: Not more than initial specified value

*ROHS Compliant