



1219 4th Avenue South  
Nashville, TN 37210

**Phone:** (615) 254-3561  
**Fax:** (615) 255-7673  
**Email:** sales@richeycap.com  
**Web:** richeycap.com

# RPT391M100V1631B

Aluminum Electrolytic Capacitors

Miniature Type  
RPT Series

Richey P/N: RPT391M100V1631B

## Specifications:

Dimensions:

Case Size D x L (mm): 16 x 31.5

Operating Temperature Range: -40-105 °C

Rated Voltage: 100 VDC

Surge Voltage: 125 VDC

Capacitance (μF): 390

Leakage Current: 390

Maximum Ripple Current: 1570 mA rms @ +105°C, 100kHz

Maximum Impedance: 0.054 @ +20°C, 100kHz


Load Life:

| Case Size >     | d - 5~6.3 | d - 8~10 | d - 12.5~18 |
|-----------------|-----------|----------|-------------|
| Voltage Range v |           |          |             |
| 6.3 ~ 10        | 4000      | 6000     | 8000        |
| 16 ~ 100        | 5000      | 7000     | 10000       |

Capacitance Change: Within +/- 25% of the initial measured value.

Dissipation Factor (tanδ): Not more than 200% of the initial specified value

Leakage Current: Not more than initial specified value



\*ROHS Compliant