



1219 4th Avenue South  
Nashville, TN 37210


**Phone:** (615) 254-3561  
**Fax:** (615) 255-7673  
**Email:** sales@richeycap.com  
**Web:** richeycap.com

# RPX472M6R3V1235B

Aluminum Electrolytic Capacitors

Miniature Type  
RPX Series

Richey P/N: RPX472M6R3V1235B



## Specifications:

Dimensions:

Case Size D x L (mm): 12.5 x 35

Operating Temperature Range: -55-105 °C

Rated Voltage: 6.3 VDC

Surge Voltage: 7.2 VDC

Capacitance ( $\mu\text{F}$ ): 4700

Leakage Current: 592.2

Rated Ripple Current: 2220 mA rms @ +105°C, 100kHz

Maximum Impedance: 0.028 @ +20°C, 100kHz

Max ESR (m $\Omega$ ): 0.079 @ +20°C, 120Hz

Load Life:

Case Size  $\leq 6.3$  8 ~ 10  $\geq 12.5$

Hours 2000 3000 5000

Capacitance Change: Within +/- 20% of the initial measured value.

Dissipation Factor ( $\tan\delta$ ): Not more than 200% of the initial specified value

Leakage Current: Not more than initial specified value

\*ROHS Compliant