



1219 4th Avenue South
Nashville, TN 37210

Phone: (615) 254-3561
Fax: (615) 255-7673
Email: sales@richeycap.com
Web: richeycap.com

RUW22RM400V1225B

Aluminum Electrolytic Capacitors

Miniature Type
RUW Series

Richey P/N: RUW22RM400V1225B

Specifications:

Dimensions:

Case Size D x L (mm): 12.5 x 25

Operating Temperature Range: -40-125 °C & -25-125 °C

Rated Voltage: 400 VDC

Surge Voltage: 450 VDC

Capacitance (µF): 22

Leakage Current: 334

Rated Ripple Current: 112 mA rms @ +125°C, 120Hz

Typical ESR (mΩ): 3.6 @ +20°C, 120Hz

Max ESR (mΩ): 9 @ +20°C, 120Hz

Load Life:


Case Size 10 12.5

Hours 4000 5000

Capacitance Change: Within +/- 25% of the initial measured value.

Dissipation Factor (tanδ): Not more than 300% of the initial specified value

Leakage Current: Not more than initial specified value



ΦD	10	12.5	16	18
F	5.0	5.0	7.5	7.5
Φd	0.6	0.6	0.8	0.8
a	2.0	2.0	2.0	2.0

*ROHS Compliant