



1219 4th Avenue South  
Nashville, TN 37210

**Phone:** (615) 254-3561  
**Fax:** (615) 255-7673  
**Email:** sales@richeycap.com  
**Web:** richeycap.com

# RUW331M200V1836B

Aluminum Electrolytic Capacitors

Miniature Type  
RUW Series

Richey P/N: RUW331M200V1836B

## Specifications:

Dimensions:

Case Size D x L (mm): 18 x 36

Operating Temperature Range: -40-125 °C & -25-125 °C

Rated Voltage: 200 VDC

Surge Voltage: 250 VDC

Capacitance (µF): 330

Leakage Current: 2050

Rated Ripple Current: 673 mA rms @ +125°C, 120Hz

Typical ESR (mΩ): 0.2 @ +20°C, 120Hz

Max ESR (mΩ): 0.5 @ +20°C, 120Hz

Load Life:


Case Size 10    12.5

Hours    4000 5000

Capacitance Change: Within +/- 25% of the initial measured value.

Dissipation Factor (tanδ): Not more than 300% of the initial specified value

Leakage Current: Not more than initial specified value



ΦD	10	12.5	16	18
F	5.0	5.0	7.5	7.5
Φd	0.6	0.6	0.8	0.8
a	2.0	2.0	2.0	2.0

\*ROHS Compliant